

Linear light Series

2835 White

114LEDs/M

Color White Indoor 120° 24V DC

80 CRI 20mm W



Combination



Parameters	114LEDs/M
Dimension	1200*20*20MM
Power	18W/PCS
Lumens	150-180LM/Watt
Voltage	24V
Cover	Microprismatic cover
IP Grade	Ip40

CCT	CRI	Efficiency LM/M
6000-6500K	>80	3000
4000-4500K	>80	3000
2800-3200K	>80	
2600-2800K	>80	3700
2400-2600K	>80	
2200-2400K	>80	
R 618-628nm		887
G 515-525nm		793
B 460-470nm		700
Y 585-595nm		887

Linear light Series

2835 White

114LEDs/M

Color White Indoor 120° 24V DC

80 CRI 16mm W



Combination



Parameters	114LEDs/M
Dimension	1200*17.5*16MM
Power	15W/PCS
Lumens	150-180LM/Watt
Voltage	24V
Cover	Milky cover
IP Grade	Ip40

CCT	CRI	Efficiency LM/M
6000-6500K	>80	3000
4000-4500K	>80	3000
2800-3200K	>80	
2600-2800K	>80	3700
2400-2600K	>80	
2200-2400K	>80	
R 618-628nm		887
G 515-525nm		793
B 460-470nm		700
Y 585-595nm		887